B NAME:				QUANTITY:	ITEM NO.:		
				PRODUCT NAME: 4" C	C/C DECK FAUCET		
					TH SWING SPOUT		
	– 7-1/2" –––– [191mm]	1		MODEL:			
			<u> </u>	🗖 26174 WITH	H 6" SWING SPOUT		
	\square		\mathcal{T}	🗖 26182 WITH	H 8" SWING SPOUT		
				26190 WITH 10" SWING SPOUT			
Ē			"A" 		H 12" SWING SPOUT		
- ⁻ -	· ₽,			🗖 26212 WITH	H 18" SWING SPOUT		
	L	— "C" ———	_ _				
L.	4"			FEATUREO			
[102mm]				FEATURES: * 4" C/C DECK	* 4" C/C DECK MOUNTED		
		1	,		ANKS WITH LOCK NUTS		
MODEL	DIM "A"	DIM "B"	DIM "C"	AND 1/2" NP	AND 1/2" NPT THREADS		
26174	2-1/8" [54mm]	4-3/4" [121mm]	6" [152mm]				
26182	2-1/2 [64mm]	5-1/4" [133mm]	8" [203mm]	SYSTEM LIMITS			
26190	3-1/8" [79mm]	5-7/8" [149mm]	10" [254mm]	PRESSURE 2	TEMP: 40 F MIN TO 140 F MAX PRESSURE 200 PSI MAX STATIC 2.20 GPM AT 80 PSI		
26204	3-5/8" [92mm]	6-3/8" [162mm]	12" [305mm]				
26212	5-3/8" [137mm]	8-3/8" [213mm]	18" [457mm]				
				SHIPPING WEI * 5.5 LBS	GHT		
ROUGH IN	N:						
		~	- ø7/8"				
	-		[22mm]				
	Ŧ	Ŧ					
	⊢ _[1	– 4" — ► 102mm]					
	SP: AN	SI/A112.18.1M					
	v Fisher Manı	ufacturing Co	mpany				
	Tulare, CA 9						